In Stock Products

ERICSON®
SAFETY IS OUR STANDARD

ALL LISTED PRODUCTS QUICK SHIP

When the unexpected happens, Ericson is ready with temporary lighting and power. Most products listed here are available for quick ship.



15-75 KVA POWER TRANSFORMATION UNITS

- cETLus listed
- UL943-5th Edition, Self-Testing GFCI
- UL1640 - Design Assembly
- NEMA 3R In Use Design

Part Number	kVA	Primary Configuration	Secondary Voltage	Secondary MCB	5-20 GFCI Duplex Receptacles	CS6369 50A	L6-30
15kVA, 3 Phase, 480-Volt Primary							
EJR4315CM31200	15	30A Disc SW w/6' Primary Cable	208Y/120	40A 3P	12	0	0
EJR24330CM31002	30	30A Disc SW w/6' Primary Cable	208Y/120	80A 3P	10	0	2
EC2-A-4345-CM3034	45	100A Disc SW w/6' Primary Cable	208Y/120	125A 3P	3	4	0
EC2-B-4375-CM3036	75	200A Disc SW w/6' Primary Cable	208Y/120	200A 3P	3	6	0

50-AMP POWER DISTRIBUTION UNITS

- cETLus listed for use in U.S. and Canada
- UL943-5th Edition Self-Testing GFCI Module with Nema 4X Test/Reset Buttons For Exceptional Damp/Wet Areas
- UL1640 – Open Neutral Protection



Poduct Number	50A inlet and Feedthrough	Environmental Rating	20 A Outlets	30 A Outlet
Straight blade NEMA 5-20, 6 circuit, 6 duplex receptacles				
1066FS	50A 240/120V CS Style	NEMA 3R	(6) NEMA 5-20, Rcpts, w/ (6) GFCI & (6) 20A C.B.	(1) NEMA L6-30, with (1) 2 pole 30A C.B.
1066FS-3C	50A 240/120V CS Style	NEMA 3R	(3) NEMA 5-20, Rcpts, w/ (3) GFCI & (3) 20A C.B.	(1) NEMA L6-30, with (1) 2 pole 30A C.B.
Compact Distribution Units 30-50-Amp				
CDU50-3R-A	50A 240/120V CS Style	NEMA 3R	(6) NEMA 5-20, Rcpts, w/ (6) GFCI & (6) 20A C.B.	(1) NEMA L6-30, with (1) 2 pole 30A C.B.

NONMETALLIC DISTRIBUTION CENTER - NM3 SERIES, 50-200-AMP, SINGLE & 3 PHASE



- UL Listed
- Rugged, Solid Rubber Construction
- Indoor and Outdoor Configurations
- UL943 5th Edition GFCI Protected Outlets

Part Number	Number of Sections	Inlet type	Phase	Volts	Amps	Main Circuit Breaker or Main Lug	Feed Thru	Receptacles
NM3-T50SL1060	1	50A CS	1	240/120V	50	ML	Y	(6) 5-20 GFCI duplex
NM3-CAMDL3120-A	2	(5) Cams	3	208Y/120V	80	ML	N	(12) 5-20 GFCI duplex
NM3-CAMDL3006-A	2	(5) Cams	3	208Y/120V	200	ML	N	(6) CS6369

15-50 AMP FACTORY ASSEMBLED CORDSETS

- Premium grade cord, jacket and construction
- Commerical & industrial grade, overmolded or factory-assembled 15-50A straight & locking blade cordsets
- Designed for rugged indoor & outdoor environments



Cord Type	Primary	Connector	Volts	Product Number		
				25′ Length	Cord Length 50′	Cord Length 100′
15-Amp Molded Cordsets						
12/3 SJTW Yellow	5-15P	5-15C Lighted	125	-	**123B**	**123D**
12/3 SJTW Yellow	5-15P	5-15C Tri-Tap Lighted	125	-	**123B-TT**	**123D-TT**
15-Amp Watertight Factory Assembled Cordsets						
12/3 SOOW Yellow	5-15P	5-15C	125	-	**1510PW6P143B**	**1510PW6P143D**
50-Amp Cordets for CDU, PDU and NM3-Series 50A PDU's , fed from CS style receptacles						
6/3+8/1 SOW/SOOW	50A CS	50-Amp California Style	125/250	**63ASO**	**63BSO**	**63DSO**

400-AMP CAM TYPE CORDSETS

- Premium grade cord, jacket and construction
- Industrial grade, factory assembled, 190-400A, locking & straight blade cordsets
- Designed for rugged indoor and outdoor environments



Amps	Cable	Product Number		
		Cord Length 25′	Cord Length 50′	Cord Length 100′
400-Amp, Single Conductor, with 4/0 W Cord - Specify CAM color				
400	4/0 Type W 2000V Black	**W40MF25-(color code)***	**W40MF50-(color code)***	**W40MF100-(color code)***
400-Amp with 4/0 SC Cord - Set of 4 Cables (CAM colors Black, Red, White, Green)				
400	4/0 SC 600V Black	**SC40MF25-4**	**SC40MF50-4**	**SC40MF100-4**

LED STRING LIGHTS



- cULus listed.
- String lights available in 50ft. and 100ft
- Designed for rapid set-up and tear down
- Supports LED lamp configurations
- Fully threaded screw shell ensures proper contact

Catalog Number	Length	Cable/Gauge	Guard Number	# of Sockets	Socket Spacing	Max Watts per socket	Primary Plug	Secondary Connector
142100	100 Ft.	14/2 SJTW 300 V	04202	10	10 ft. Centers	150 Watt	NEMA 1-15	Blunt
143100	100 Ft.	14/3 SJTW 300 V	04202	10	10 ft. Centers	150 Watt	NEMA 5-15	NEMA 5-15

1006 LED BAYLIGHT, 100-150 WATT



- cULus listed to UL153, CSA C22.2 No. 250.4
- IP64 damp location, under roof rated
- 5000K Color Temp
- Isolated constant current power supply. 6000V surge protection
- Adjustable Light Output Switch (100%, 50%, Off)
- Stainless steel guard for impact protection

Part Number	Input Voltage	Input Wattage	Primary*	Secondary	Lumens	CCT	Efficiency	Operating Temperature	CRI	Listing
1006-LED-100-16315-120	120 VAC*	100W	15 ft. molded 5-15 Plug	1 ft. molded 5-15 Conn	12,000	5,000K	120 LPW	-40° C to 60° C	>80	cULus
1006-LED-150 16315-120	120 VAC*	150W	15 ft. molded 5-15 Plug	1 ft. molded 5-15 Conn	18,000	5,000K	120 LPW	-40° C to 60° C	>80	cULus

PORTABLE POWER & GFCI OPTIONS



- UL 943 5th Edition & CSA C22.2 No.144.1, self-testing GFCI
- NEMA 4X & 6P – Watertight and Temporary Submersion
- Manual and Automatic Reset
- 14 & 12ga. 15 & 20A 125V
- Several Configurations – Tri-Tap, Y & W, WP Box, Explosion Proof Plug & Connector

Part Number	Length (ft.)	Primary	Secondary	Amps	Watts	NEMA Rating
XG2-14-2S	2 ft.	Molded NEMA 5-15	Molded NEMA 5-15	15	1800	NEMA 6P (Housing only)
XG2-14-25S	25 ft.	Molded NEMA 5-15	Molded NEMA 5-15	15	1800	NEMA 6P (Housing only)
XG2-12-2TT	2 ft.	Molded NEMA 5-15	Molded NEMA 5-15 Tri-tap	15	1800	NEMA 6P (Housing only)
XG2-12-50TT	50 ft.	Molded NEMA 5-15	Molded NEMA 5-15 Tri-tap	15	1800	NEMA 6P (Housing only)
XG2-12-2W-15	2 ft.	Watertight NEMA 5-15	Watertight NEMA 5-15	15	1800	NEMA 6P

TUFFTRAXX™

CABLE PROTECTOR WITH "T" CONNECTOR - INDUSTRIAL DUTY

- Meets OSHA & NEC Requirements
- Industry leading load ratings up to 50,000 lbs. per axle
- Industrial and Extreme duty options
- Constructed from lightweight polyurethane
- Custom base and cover colors available
- Compatible with industry manufacturers



Part Number (Base color shown)	Number of channels	Length	Width	Height	Channel Width	Channel Height	Weight (lbs)	Load Rating per axle (lbs)
Industrial Duty - Yellow Base, Blue Lid								
CP3-36-ED	3	36.0"	20.0"	3.1"	2.2"	2.3"	29.5	50000
CP5-36-ED	5	36.0"	19.5"	2.3"	1.4"	1.3"	23.5	50000
CP5-36-ID	5	36.0"	17.3"	2.0"	1.4"	1.3"	20.6	27000
Industrial Duty - Black Base, Blue Lid								
CP5-36-ID-BKBL	5	36.0"	17.3"	2.0"	1.4"	1.3"	20.6	27000

CABLE PROTECTOR WITH "DB" CONNECTOR - INDUSTRIAL DUTY

NEW!

- Meets OSHA & NEC Requirements
- Industry leading load ratings up to 27,000 lbs. per axle
- Constructed from lightweight polyurethane
- Custom base and cover colors available
- Compatible with industry manufacturers



Part Number (Base color shown)	Number of channels	Length	Width	Height	Channel Width	Channel Height	Weight (lbs)	Load Rating per axle (lbs)
Industrial Duty - Black Base, Blue Lid - DB connector								
CP5-36-ID-BKBL-DB	5	36.0"	19.8"	2.0"	1.3"	1.3"	21.6	27000

ERICSON®
SAFETY IS OUR STANDARD
Ericson Manufacturing Company
4323 Hamann Parkway
Willoughby, OH 44094, USA

CERTIFIED ISO 9001 COMPANY
1-800-ERICSON
info@ericson.com
L1000909C
ericson.com